

How to order

Without switch (built-in magnet for switch)

HLC - **20CS** - **L1**

With switch (built-in magnet for switch)

HLC - **20CS** - **L1** - **T2H** - **R**

A Size

B Option

C Switch model No.
* indicates the lead wire length.

D Switch quantity

[Example of model No.]

HLC-20CS-L1-T2H-R

Model: Thin long stroke parallel hand

- A** Size : 20CS
- B** Option : Long stroke 1
- C** Switch model No.: Proximity T2H switch, lead wire 1 m
- D** Switch quantity : 1 on open side

Code	Description
A Size	
08CS	
12CS	
16CS	
20CS	
25CS	
30CS	
B Option	
	Size 08CS 12CS 16CS 20CS 25CS 30CS
Blank	Standard ● ● ● ● ● ●
L1	Long stroke 1 ● ● ● ● ● ●
C Switch model No.	
Axial lead wire	Radial lead wire
T2H*	T2V*
T3H*	T3V*
* Lead wire length	
Blank	1 m (standard)
3	3 m (option)
5	5 m (option)
D Switch quantity	
R	1 on open side
H	1 on closed side
D	2

LCM
LCR
LCG
LCW
LCX
STM
STG
STS/STL
STR2
UCA2
ULK*
JSK/M2
JSG
JSC3/JSC4
USSD
UFCD
USC
UB
JSB3
LMB
LML
HCM
HCA
LBC
CAC4
UCAC2
CAC-N
UCAC-N
RCS2
RCC2
PCC
SHC
MCP
GLC
MFC
BBS
RRC
GRC
RV3*
NHS
HRL
LN
Hand
Chuk
MechHnd/Chuk
ShkAbs
FJ
FK
SpdContr
Ending
LSH-HP
LSH
FH100
BSA2
BHA/BHG
LHA
LHAG
HAP
HKP
HCP
HGP
HLF2
HLAG/HLBG
HLAG/HLBG
HLC
HLD
HMF
HMF-G
HMFB
HFP
FH500
HBL
HJL
HMD
HDL
HJD
BHE

How to order switch

SW - **T2H**

Switch model No.
(Item **C** above)

Specifications for rechargeable battery (Catalog No. CC-1226A)

HLC - ... - **P4*** ● Design compatible with rechargeable battery manufacturing process.

* Contact CKD for details.